

**Product Features VOIP SIP**

ADSL Compliant: ANSI T1.413 issue 2, ITU G.dmt (G.992.1), ITU G.lite (G.992.2) ADSL over POTS (Annex A) or ADSL over ISDN (Annex B/UR2), G.994.1 (G.hs, Multimode), Maximum downstream rate up to 8 Mbps, Maximum upstream rate up to 1 Mbps

ATM Protocols and Encapsulations: Up to 8 PVCs (Permanent Virtual Circuit), ATM supports AAL5, UBR & CBR, RFC 2516 (PPP over Ethernet), RFC 2364 (PPP over ATM), RFC 1577 (Classical IP over ATM) (F4 on all VPIs, F5 on VPI 0 only) VPI (0-255), VCI (0-65535)

Bridging/Routing: Ethernet to ADSL self-learning Transparent Bridging (IEEE 802.1D), Supports up to 128 MAC learning address, IP routing-RIPv2 (backward compatible with RIPv1), Static routing DHCP Server and Client, NAT, NAT, ICMP, IGMP

Security and HTTP Web-based Management: PAP, CHAP, User authentication for PPP, Configuration of NAT/NAPT WAN and LAN connection statistics, Configuration of VCs (Virtual Circuits), DNS Proxy DMZ support, MAC Filtering, ALG supports MSN Messenger 4.x, H.323 (MS NetMeeting), IPSec, PPTP VPN pass-through, L2TP VPN pass through, HTTPS, HTTP, FTP, ICMP, SMTP, POP3, NNTP, Telnet, Age of Empires 2, StartCraft

**NAGISAN COMMUNICATION SDN BHD (657712-W)**

NO: 42-3A, JALAN EMAS- 5 TAMAN EMAS CHERAS 43200 SELANGOR MALAYSIA.

TEL:+603 90765680 90765681 FAX:+603 90765861

www.nagisan.com email: ravi@nagisan.com