

IPG168 SIP/H323/MGCP/IAX2 Life Line Voice Gateway

Features

- Internet to Internet and Internet to Phone dialing capabilities via ITSP.
- H.323 V4, MGCP, SIP, IAX2, Net2phone private protocol.
- Audio codec G.711a/u, G.723.1, G.729, GSM.
- DHCP support for LAN or Cable modem.
- PPPoE support for ADSL or Cable modem.
- Set configuration by HTTP web browser (IE6.0) or Telnet, Upgrade by FTP.
- VAD (Voice active detect).
- CNG (Comfort noise generation).
- Dynamic voice jitter buffer.
- G.168/185 compliant 18ms echo cancellation.
- Tone generation and Local DTMF re-generation according with ITU-T.
- E.164 dial plan and customized dial rules.
- Adjustable volume for both handset and speaker.
- Voice prompt.

Models Available

- IPG168V - Single RJ45 Port, 2 RJ11 Ports.



Package Contents

- VoIP Gateway.
- Power Adaptor.
- CD including Setup Guide and firmware.

General Specifications

Network Interface	: 1 RJ-45 Ethernet port.
Tel Interface	: 2 RJ-11 Ports.
Voltage	: DC 9V-12V
Power Adaptor	: DC 12V / 450mA
Dimensions	: 150 x 110 x 28 mm (L x W x H)

Environmental

Operating Temp	: 0 - 50 (Celsius)
Storage Temp	: -30 - 65 (Celsius)
Humidity	: 10% - 90% non-condensing



NAGISAN COMMUNICATION SDN BHD (657712-W)

NO: 42-3A, JALAN EMAS- 5 TAMAN EMAS CHERAS 43200 SELANGOR MALAYSIA.

TEL:+603 90765680 90765681 FAX:+603 90765861

www.nagisan.com email: ravi@nagisan.com